Product number 3738 3748 3762 3764 3792 Properties/suitable for Wood Electronics Cardboard Plastics Universal Key features (info box)

| Physical and Performance Characteristics, Key Features | | | | | | | | |
|--|------------------------|------------------------|------------------------|------------------------|------------------------|--|--|--|
| Product number | 3738 | 3748 | 3762 | 3764 | 3792 | | | |
| Base | Thermoplastic adhesive | | | |
| Colour | Tan | White | Tan | Clear | Clear | | | |
| Open time [seconds] | 50 | 45 | 35 | 40 | 50 | | | |
| Ball and ring melt point | 86 °C | 144 °C | 94 °C | 88 °C | 83 °C | | | |
| Peel strength [Newton/cm] | 23 | 32 | 12 | 25 | 23 | | | |
| Shear strength [MPa] | 2.6 | 2.2 | 3.8 | 2.7 | 1.7 | | | |
| Wood | • | | | | | | | |
| Electronics | | • | | | | | | |
| Cardboard | | | • | | | | | |
| Plastics | | • | | • | | | | |
| Universal | | | | | • | | | |

| Suggested Applications | | | | | | | |
|--|------|------|------|------|------|--|--|
| Product number | 3738 | 3748 | 3762 | 3764 | 3792 | | |
| Woodworking and furniture manufacturing | • | | | | • | | |
| Upholstery | • | | | | • | | |
| Cabinetry | • | | | | | | |
| Point-of-purchase displays | • | | • | | • | | |
| Electronic applications such as potting and wire tacking, and bonding | | • | | | | | |
| Transportation interiors | | • | | | | | |
| Seating attachment | | • | | | | | |
| Manual and corrugated carton sealing | | | • | | | | |
| General packaging applications | | | • | | | | |
| Repacking chipboard | | | • | | | | |
| Trade exhibits | | | • | | | | |
| Mounting and trim attachment | | | | • | | | |
| Assembly, attaching, repairing, potting, panel bonding, wire tacking, bundling, sealing, encapsulating | | | | • | | | |
| Panel bonding | | | | | • | | |
| Product number | 3738 | 3748 | 3762 | 3764 | 3792 | | |

Product Use