

Specifications

Fire Rating

Fire Rating Euroclass B-s2

Application Type

Application Displays
Opaque Signs
Point of Sale
Public Transport
Signmaking
Vehicle Marking

Interior or Exterior use Interior
Exterior

Adhesive & Liner

Adhesive Grey, repositionable with air egress
Adhesive Composition Water-based acrylic
Adhesive colour Grey
Adhesive Strength 16N/25mm
Adhesive Type Pressure Activated
Adhesive Technology 3M Comply™
3M Controltac™
Removability Permanent
Repositionable
Material used as liner Back-sided Polyethylene coated paper
Liner Colour White

Temperature Resistance

Minimal Temperature Resistance -50°C
Maximal Temperature Resistance 90°C

Application Specifications

Curve Flat surfaces
Format Slightly curved surface

Dimensions

Thickness 80µ

Material Ink Compatibility

Ink Type Solvent
Eco-Solvent
UV-Cured
Latex

Product Storage

Shelf Life Use within two years from the date of manufacture on the sealed original box. Use within one year after opening the box.

Storage & Transport conditions +4°C to +40°C, out of sunlight, original container in clean and dry area.

Application Temperature

Minimum Application temperature 10°C

Durability

Durability (range) 5 years

Product Type

Product Type Non-PVC polymer