

# Specifications

## Application Type

---

<b>Application</b>	Protection
<b>Interior or Exterior use</b>	Exterior Interior

## Adhesive & Liner

---

<b>Adhesive</b>	Pressure sensitive, clear, solvent based
<b>Adhesive Composition</b>	Solvent-based acrylic
<b>Adhesive colour</b>	Clear
<b>Adhesive Type</b>	Pressure-sensitive
<b>Removability</b>	Permanent
<b>Material used as liner</b>	Polyester
<b>Liner Colour</b>	Clear

## Temperature Resistance

---

<b>Minimal Temperature Resistance</b>	-54 °C
<b>Maximal Temperature Resistance</b>	107 °C

## Application Specifications

---

<b>Curve Format</b>	Curved surfaces Corrugated surfaces Flexible substrates Rivets Slightly curved surface
---------------------	--

## Dimensions

---

<b>Thickness</b>	50 µ
------------------	------

## Product Storage

---

<b>Shelf Life</b>	Total shelf life: 3 years from the date of manufacture on the original box. If you do process the film, do so within 2 years and apply within 1 year. If you do not process the film, apply it within 3 years.
<b>Storage &amp; Transport conditions</b>	4°C to 30°C, • Out of sunlight • Clean dry area • Original container • Bring the product to print room temperature before using

## Durability

---

<b>Durability (range)</b>	8 years
---------------------------	---------

## Surface Type

---

<b>Surface Type</b>	Curved surfaces Corrugated surfaces Rivets
---------------------	--

## Product Type

---

Product Type

Cast