

# Specifications

## Application Type

---

|                                 |                                       |
|---------------------------------|---------------------------------------|
| <b>Application</b>              | Car wrap<br>Vehicle Marking<br>Trucks |
| <b>Interior or Exterior use</b> | Exterior<br>Interior                  |

## Adhesive & Liner

---

|                            |                             |
|----------------------------|-----------------------------|
| <b>Adhesive Strength</b>   | 20 N/25mm                   |
| <b>Adhesive Type</b>       | Pressure Activated          |
| <b>Adhesive Technology</b> | 3M Comply™                  |
| <b>Removability</b>        | Repositionable<br>Removable |

## Temperature Resistance

---

|                                       |        |
|---------------------------------------|--------|
| <b>Minimal Temperature Resistance</b> | -60 °C |
| <b>Maximal Temperature Resistance</b> | 107 °C |

## Application Specifications

---

|                     |   |
|---------------------|---|
| <b>Curve Format</b> | Corrugated surfaces<br>Curved surfaces<br>Flat surfaces<br>Rivets |
|---------------------|---|

## Dimensions

---

|                  |      |
|------------------|------|
| <b>Thickness</b> | 50 µ |
|------------------|------|

## Material Ink Compatibility

---

|                 |                   |
|-----------------|-------------------|
| <b>Ink Type</b> | Latex<br>UV-Cured |
|-----------------|-------------------|

## Application Temperature

---

|  |       |
|--|-------|
| <b>Minimum Application temperature</b> | 10 °C |
|--|-------|

## Durability

---

|                           |                |
|---------------------------|----------------|
| <b>Durability (range)</b> | Up to 12 years |
|---------------------------|----------------|