



VUFLEX FRONTLIT PREMIUM

ROLL WIDTH	-	760mm/1100mm/1370mm/1600mm/3200mm
ROLL LENGTH	-	30m/60m
BASE FABRIC	-	HT PES DIN ISO 60001
TYPE OF COATING	-	PVC
WEIGHT	-	550G
COLD RESISTANCE	-	-30 C
HEAT RESISTANCE	-	+ 70 C
LIGHT FASTNESS	-	TO DIN 54004
TENSILE STRENGTH	-	2300/2300 N/5cm
TEAR RESISTANCE	-	250/280 N
CRACK RESISTANCE	-	TO DIN 53359 A
FIRE RETARDENCY	-	B1 NFPA-701
FINISH	-	SMOOTH MATT PR LACQUER BOTH SIDES
INK COMPATABILITY	-	ECOSOL, LATEX, SOLVENT, UV AND LED CURABLE
APPLICATION	-	GRAND FORMAT BANNERS, BILLBOARDS AND EXHIBITION GRAPHICS

THIS PRODUCT HAS BEEN PRODUCED FOR DIGITAL INK JET PRINTING, BUT CUSTOMERS MUST SATISFY THEMSELVES THAT THE PRODUCT WILL PERFORM TO THEIR REQUIREMENTS BY TESTING PRIOR TO A PRODUCTION RUN TAKING PLACE.

SPECIFICATION DETAILS ARE OFFERED IN GOOD FAITH, BUT WILL NOT BE ACCEPTED IN MATTERS OF ARRANTY