

# StreetRap

White matt calendered PVC film specially designed for bitumen applications, 85 µm for outdoor sidewalk and parking lot floor graphics.

SPECIALLY DESIGNED FOR

- **\*Bitumen applications**
- **\*Outside floors**

Overview:

- TECHNOLOGY  
Polymeric PVC
- THICKNESS  
85 µm
- ADHESIVE PERFORMANCE  
High tack
- DURABILITY OUTDOOR  
3-6 month(s)
- FIRE RATING  
C-s1,d0 (EN 13501-1)

More details:

FACE

- *Technology*

**Polymeric PVC**

- *Thickness*

**85 µm**

- *Finish*

**white matt**

COMPATIBILITY

- *Surface(s)*

**Flat/2D, Riveted/3D, Curved**

- *Support(s)*

**Asphalt / Bitumen**

- *Print Method*

**Eco-solvent, Latex, Solvent**

#### DURABILITY

- *Outdoor*

**3-6month(s)**

#### ADHESIVE

- *Type*

**Acrylic solvent**

- *Performance*

**High tack**

#### LINER

- *Type*

**Coated Kraft Liner**

- *Thickness*

**160Gr/sqm**

#### MARKET SEGMENTS (APPLICATIONS)

- Public places
  - Exhibition
  - Floor graphics
  - Signage & Marking
-