

FloorInOne 225 225STFG

Self Adhesive Graphic Fabric with Textured Vinyl Coating

Applications

- Floor graphics
- Semi and permanent wall graphics

Benefits

- Suitable for almost all indoor floors and walls like carpets, vinyl, ceramic, tiles, wood laminate flooring, smooth-polished concrete...
- Also suitable short term outdoor on smooth floors
- No lamination required
- Easy to apply, reposition and remove
- R12 (slip resistance) and B1 (fire rating) certified

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "gas-out" after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitiser Group of Companies



Printability:



Thickness:



Available widths:

