
FLOOR-IN-ONE 225 225STFG

HIGH PERFORMANCE INKJET MEDIA FOR LATEX, SOLVENT & UV PRINTERS

KERNOWJET®
LATEX, SOLVENT & UV

FEATURES

- Suitable for almost all indoor floors and walls like carpets, vinyl, ceramic, tiles, wood laminate flooring, smooth-polished concrete...
- Also suitable short term outdoor on smooth floors
- No lamination required
- Easy to apply, reposition and remove
- R12 (slip resistance) and B1 (fire rating) certified

SIZES

Available in widths of: 1220mm

Thickness (500µ/19.7mil) Weight (385gsm)

Available in UK only

APPLICATIONS

- Floor graphics
- Semi and permanent wall graphics

GENERAL

Recommended Conditions:

Printroom	15°C – 30°C	30% – 65% RH
Usage	-40°C – 80°C	10% – 90% RH
Storage	10°C – 20°C	20% – 50% RH

Shelf Life: 12 months after delivery (under recommended storage conditions)

Durability

The durability of Floor-in-One is dependent on the inks used, surface applied and the amount and type of foot traffic. We recommend –A maximum use of 2 months for low-traffic, indoor floor applications with UV inks, one month for latex inks and three weeks for solvent inks, 3-24 months for walls and non-pedestrian applications (UV, latex or solvent inks)

A maximum use of 1 week for outdoor applications on smooth surfaces e.g. polished concrete but is not designed for road traffic or stone-filled surfaces such as asphalt or rough, screeded concrete. Furthermore, it also depends on the mechanical use of the surface where it is applied.

Floor-in-One must be applied to clean, dry, smooth surfaces above freezing (e.g will not adhere to a frosted or wet/damp surfaces)

COMPATIBILITY

Mild Solvent	Eco Solvent	Latex	UV Cured
***	***	***	***