

HIGH PERFORMANCE INKJET MEDIA FOR LATEX, SOLVENT & UV PRINTERS

**KERNOWJET®**

**LATEX & SOLVENT**

---

## FEATURES

---

- **Unique sharkskin coating absorbs the ink & dries tough**
  - **Eliminates the need to laminate**
  - **Sharkskin structure gives great color gamut and high grip; R10 certified**
  - **Easy to apply & easy to remove, does not tear into small pieces when removing**
  - **No shrinkage – no risk of a rim of dirty adhesive forming around the print**
  - **Ultra-tough polyester base, resists tearing, resists pallet trucks & stiletto heels**
  - **Certified fire rating BFL-s1**
- 

## SIZES

---

Available in widths of: 1372mm & 1524mm

Thickness: 170µ

Adhesion: AFTER 24H 11 N/25mm

---

## APPLICATIONS

---

- **Indoor floor graphic displays**
  - **Supermarkets, shopping malls, convention centres, airports**
  - **All smooth hard floors e.g. concrete & tiling**
  - **Low Pile Carpet tiles**
- 

## GENERAL

---

[Installation Instructions](#)

Recommended Conditions:

Printroom	15°C – 30°C	30% – 65% RH
Usage	-40°C – 80°C	10% – 90% RH
Storage	10°C – 20°C	20% – 50% RH

Shelf Life: 12 months after delivery (under recommended storage conditions)

---

## COMPATIBILITY

---

Solvent

Latex

UV

\*\*\*

\*\*\*

\*\*\*