



Opaline Gloss 201 201SGB

Gloss Backlight Polyester Film

Applications

- Lightboxes
- Backlit applications indoor and outdoor

Certified for
HP Latex Inks

Benefits

- Front print on high-gloss high-resolution coating
- Bright light-diffusing back-coat hides light elements
- Optimum day/night performance
- Superb gamut when back or front-lit
- Weather resistant for outdoor displays
- Scratch resistant for scrolling displays
- Antistatic treatment avoids attracting dust and slipping in the printer

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Printability:

(Eco) Solvent ✓✓✓

Latex* ✓✓✓

UV ✓✓✓

Thickness:

201 **7.9** **285**
μ mil gsm

Available widths:

914 **1067** **1270**
36" 42" 50"

1372 **1524**
54" 60"

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitiser Group of Companies

* from 3rd Gen HP or later